NO:S2DZDA20MV0

2D Image Barcode Scanner User Manual

Factory Default

Version

V1.0

Interface

USB

Rs232

USB-COM

Scan Mode

Manaul

Successive scanning

Auto-Condutction

Trigger command mode

Suffix Settings

*Enter

Enter and Line

TAB

None

Sleep time settings

*Sleep time ON

Sleep time OFF

Note: When "Sleep time On"selected, in Manual mode, scanner will enter sleep mode after 30S, can worked by press the key of scanner

Buzzer

*Sound ON

Sound OFF

High

*Mid

Low

USB Country Keyboard types

*USA

Czech

Franch

German

Hungary

Italy

Janpan

Spain

Image Reverse

ON

OFF

Custom prefix Prefix Settings

Add prefix

*Delete Prefix

Modify prefix

Scan "Modify prefix", and data code, the user can modify the prefix content

Custom prefix Suffix Setting

Add Suffix

*Delete Suffix

Modify Suffix

Scan "Modify Suffix" and scan data code, user can modify the suffix conten

Output Data Coding mode

In order to allow the host to print Chinese data in the specified encoding format, Can be set by reading the output data encoding format

Note: GBK format can be used for notepad, UNICODE format can be used WORD and chat tools commonly used input box, BIG5 format support traditional Chinese

*Output GBK type

Output UNICODE type

Output BIG5 type

Output UTF-8 type

Input Data Encoding mode

In order to allow the scanner to read a variety of encoding formats, Bar code can be read by the "input data encoding format" to set up

*Input GBK type

Input UNICODE type

Input AUTO type

Input UTF-8 type

Baud

4800

9600

19200

38400

57600

115200

Number Appendix

0

1

2

3

4

5

6

7

8

9

A

B

C

D

E

F

Save

Cancel one data before read

Cancel a string of data before read

Cancel Settings